

## EMERGENCY MONITORING PANEL

-  Restroom 1
-  Restroom 2
-  Restroom 3
-  Restroom 4
-  Restroom 5
-  Recreational Room
-  General Purpose Room
-  Store



Schonell

The Schonell Alerte is an innovative, fully integrated hardwired wireless emergency call system for small to medium setup. When an emergency occurs, a simple press of the emergency button triggers an alarm on the Emergency Monitoring Panel, and help will be on the way.

The labeled LED indicators provide at-a-glance information on the emergency location.

Our system can be used for various applications, such as residential homes, medical wards, elderly homes, community toilets, government organizations, or kindergarten classrooms.

## Model: Emergency Alerte Control Panel

8 Channel LED light Indication with Alarm Buzzer, supports up to 8 emergency buttons per panel  
Labeled indicators provide at-a-glance information during emergency  
Press button to mute alarm  
Water and Weather Resistant

Dimensions: 130x120x35mm  
Material: Aluminium and stainless steel button  
Electrical Supply: DC12V2A  
Power Consumption: 2.5W  
Recommended operating temperature range: 0 to 40°  
Relative humidity: up to 95% non-condensing  
Buzzer Alarm Output: Approx. 90dB  
Comes with Power Adaptor  
Continuous or pulse-tone buzzer alarm output



## Model: Alerte Button

IP55 button, press for emergency, insert key to release

Dimensions: 86x86x32mm (Flushed)  
Material: Aluminium and Polycarbonate (Fireproof)  
Electrical Supply: DC12V1.25A  
Recommended Operating Temperature Range: -25 to 55°



## Model: Alerte Push Button (Heavy Duty)

IP55 button, push for emergency, turn to release, heavy duty

Dimensions: 66x66x50mm (Button height: 32mm), 78x72x65mm (Button height: 32mm)  
Material: ABS plastic (White/ Yellow)  
Electrical Supply: AC660V 10A  
Recommended Operating Temperature Range: -25 to 55°



## Model: Alerte Pull Cord

IP55 pull cord, push for emergency, turn to release

Dimensions: 86x86x32mm (Flushed)  
Material: Aluminium and Polycarbonate (Fireproof)  
Electrical Supply: AC660V 10A  
Recommended Operating Temperature Range: -25 to 55°



## Model: Alerte Alarm

IP55 Individual LED Light overdoor Indication with alarm buzzer

Dimensions: 86x86x32mm (Flushed)  
Material: Aluminum and Polycarbonate (Fireproof)  
Electrical Supply: DC12V2A  
Power Consumption: 2W  
Recommended operating temperature range: 0 to 40°  
Relative humidity: up to 95% non-condensing  
LED crystal Emitting Color: Red  
Luminous Efficiency: 90-110 lm/W  
Beam Angle: 120°  
Buzzer Alarm output: Approx. 90dB  
Continuous or pulse-tone Alarm

